

NXG-433

Aritech Reliance XR Series wireless receiver 433 MHz



INCREASING ZONE CAPACITY

The NXG-433 wireless receiver adds wireless capabilities to the Aritech Reliance XR Series of panels. The receiver acts as a zone expander and supports most of the legacy 433 MHz 63-bit transmitters and functions as well as the new generation of 433 MHz transmitters and 2-way devices. The number of wireless sensors and keyfobs that can be added depends on the Aritech Reliance XR panel model. The NXG-433 wireless receiver also provides two wired zone inputs and one programmable relay output.

2 -WAY WIRELESS

The NXG-433 wireless receiver makes it possible to extend the Aritech Reliance XR Series of panels with wireless indoor & outdoor sirens, wireless input/output modules as well as 2-way keyfobs, all of these using the latest LoNa technology. The wireless communication is fully encrypted, avoiding unauthorised interference.

INSTALLATION & PROGRAMMING

The NXG-433 wireless receiver needs to be installed outside the Reliance XR Series panel housing in order to assure a maximum wireless range. The wireless receiver enrolls as a standard zone expander and will send incoming RF packets from the wireless transmitters to the panel for further processing. The Reliance XR Series wireless solution will monitor the status and presence of each wireless device and will respond in case of an RF jamming condition. The firmware of the module is remotely upgradeable via the DLX900 software.

FEATURES

- RS-485 bus receiver
- Two wired zone inputs
- One programmable SPDT Form C relay output
- Supports legacy 63-bit 433 MHz and 80-bit 433 MHz (LoNa) transmitters
- Supports LoNa wireless indoor & outdoor siren and wireless input/output module
- Learn-mode technology
- Removable terminals
- EN50131-1/EN50131-3/EN50131-6 Grade 2 Class II , INCERT T031, NFA2P
- Firmware upgrade via DLX900 over the network

NXG-208N

Aritech Reliance XR Series
wireless receiver 433 MHz

National Sales Enquiries
10 Ferntree Place
Notting Hill, Victoria 3168
Phone: 1300 361 479
Outside Australia: +61 3 9239 1200
www.fireandsecurityproducts.com.au

TECHNICAL SPECIFICATIONS

System

Product line	Aritech Reliance XR Series
Kit	No
433 MHz 63-bit protocol	legacy range of 433 MHz transmitters
433 MHz 80-bit (LoNa) protocol	new range of 433 MHz transmitters and 2-way devices

Inputs

Onboard inputs	2
NXG-8, NXG-9(-RF)	3.3K - 6.6K; 4.7K - 9.4K - 19.4K; 4.1K - 8.2K - 16.4K
Tamper input	Normally closed

Outputs

No. of onboard outputs	1
------------------------	---

Communication

Databus type	RS485
--------------	-------

Electrical

Operating voltage	12 VDC (from approved power supply unit)
Current consumption	47 mA (typical) 51 mA (maximum)

Physical

Physical dimension	155 x 95 x 26 mm
Shipping weight	160 g

Environmental

Storage temperature	-10° to 55°C
Relative humidity	90% relative humidity non-condensing

Regulatory

EN50131 Grade	Grade 2
Compliance	CE
Certification	EN50131 Grade 2, INCERT, NFA2P



Specifications subject to change without notice.
Carrier Fire & Security Australia Pty Ltd.
© 2023 Carrier. All rights reserved. All trademarks are the property of their respective owners.

